

Professional Composite Safety Shoes

Model: L-7328 Engineer | ProEngineer



**Toe Cap
Protection**



**Anti
Penetration**



**Slip
Resistance**



Lightweight



Antibacterial



**Heavy Duty
Outsole**

Technical Specifications

Upper	Smooth Cow Leather
Lining	BactiVoid™ Sandwich Mesh
Insole	Anti-Fatigue Memory Foam Insole
Outsole	Slip-Resistant & Durable PU/PU Outsole
Toe Cap	VortiGard™ Composite Toe Cap (200J)
Midsole	FlexBarrier™ Puncture Protection (1100N)
Size Range	EU 37–47 UK 3–13 US 4–14
Weight	Approx. 580g / shoe (EU42)

Certifications & Standards

	EN ISO 20345:2022+A1:2024 S3S SR FO
	ASTM F2413-24 I/C PR SD100

Performance Notes

- **SR:** Slip Resistance Tested on Ceramic Tile with Glycerol
- **FO:** Fuel Oil Resistant Outsole
- **Anti-Static:** Electrical Resistance 100kΩ–1000MΩ



VortiGard™ Composite Toe Cap (200J)
Non-metallic Protection
Against Impact Hazards.



FlexBarrier™ Puncture Protection (1100N)
Flexible Penetration Protection
with Lightweight Comfort.



Slip-Resistant & Durable Outsole
Excellent Grip, Wear Resistance and
Oil Resistance

Recommended Applications:



Facility
Management



Engineering
Support



Maintenance



Warehousing



Logistics



Outdoor Work



**Scan for
More Information**

www.safetoe.net